

Tableau des dimensions

											
m	mm	mm	mm	mm	mm	mm	mm	mm	mm		
15	120	410	600	145	500 et 1250	213x250	560	400	32/30 x 1090	2	1,2
16		430				256x250				2,1	1,2
18		470				269x300				2,2	1,3
20		510				295x350				2,3	1,4
22		550				348x350				2,4	1,5
							Ø880	Ø700	8x32/30 x 1090		

Tableau des tenues mécaniques selon la norme EN 40

H	Poids	1 CII	1 CI	2 CII	2 CI	3 CII	3 CI	4 CII	4 CI	5 CII	5 CI	M	T
m	kg	m²	m²	m²	m²	m²	m²	m²	m²	m²	m²	daN. m	daN
15	75	4,18	2,97	3,41	2,51	2,63	2,01	2,11	1,66	1,43	1,07	10832	1081
	150	3,88	2,75	3,15	2,32	2,43	1,84	1,94	1,52	1,29	0,96	10853	1100
16	75	4,06	2,88	3,30	2,43	2,54	1,94	2,04	1,62	1,41	1,05	12195	1168
	150	3,75	2,65	3,05	2,23	2,34	1,77	1,87	1,48	1,27	0,93	12169	1186
18	75	3,81	2,70	3,10	2,27	2,39	1,81	1,91	1,51	1,30	0,95	14799	1333
	150	3,53	2,49	2,86	2,08	2,19	1,66	1,74	1,37	1,19	0,83	14773	1357
20	75	3,61	2,55	2,92	2,14	2,24	1,69	1,79	1,41	1,21	0,83	17464	1503
	150	3,33	2,35	2,70	1,97	2,07	1,56	1,64	1,28	1,07	0,71	17433	1532
22	75	3,43	2,42	2,78	2,03	2,12	1,61	1,68	1,32	1,08	0,69	20337	1687
	150	3,17	2,22	2,56	1,86	1,95	1,46	1,55	1,19	0,94	0,58	20351	1726